


IOP-PERFO Fittings for putting in automatic watering and / or lighting systems.

Simply on request, we can adapt the containers to suit your requirements: perforations, cut-outs, waterproof risers, etc.

Contact us when you place your order.

IOP-PERFO: € 10 - 30
Excl tax/ Planter depending on complexity




IOP-SH
IOP-SH40
IOP-SH60 Horticultural system.

Drainage system offering a water reservoir.
IOP-SH: 5L/m² reservoir, EPS panel, 40mm thick.
IOP-SH40: 8,7L/m² or 16L/m² reservoir according to the installation direction, recycled PEHD panel, 40mm thick.
IOP-SH60: 6cm of reservoir, approx. 23L/m² when full of agregats, recycled PEHD panel, 60mm thick.

IOP-SH & IOP-SH40 replace the drainage section made of clay pellets / pozzolana. Cover with geotextile before adding substrate. IOP-SH60 as to be full of clay pellets (approx. 45L/m²). It can be used with a water level indicator IOP-INE.

IOP-SH: € 40
Excl. tax/ container
IOP-SH40: € 50
Excl. tax/ container
IOP-SH60: € 60
Excl. tax/ container




IOP-INE Water level indicator.
40 / 50 / 60 / 70
/ 80 / 90 / 100

For pots used indoors which have a watertight base. The float indicates the water level at the bottom of the container. It allows the monitoring of watering.

Suitable for Indoor plant containers which have a watertight base. Price varies according to the height of the container.

€ 25 – 43 Excl. tax
/ container
acc. to height of container




IOP-RL Installation on casters for handling.
50 / 65 / 100FC

Concealed under the container, the casters are not visible. They allow the plant container to be moved from time to time. As they are concealed, the casters cannot be fitted with brakes. If needed, provide a brake by retractable foot in option : IOP-PFE.

May only be used on a flat, smooth and firm surface.
Beware of the risk of instability on <40cm width containers. Check the compatibility with the intended use; contact us.

€ 110 – 170 Excl. tax
/ container acc. to size

With brakes IOP-PFE :
+ € 80 – 100 Excl. tax
/ container acc. to size




IOP-PLOT Installation on adjustable PVC pedestals.
28-40 / 40-55 /
85-140 ...

For a well-balanced installation, with a uniformly distributed load. Allows water to flow underneath the container, a good ventilation and also allows adjustments in the alignment of linear arrangements of containers.

Suitable for > 40 cm wide containers. Suggested ranges of adjustment : 12 / 15 / or 55 mm. Others on request.

€ 55 – 65 Excl. tax
/ container
acc. to std ranges, others on request



IOP-PR Installation on adjustable feet.

For installation on sloping ground.

Replaces IOP-PLOT for < 40 cm wide planters.

€ 120 – 140 Excl. tax
/ container acc. to size & slope




IOP-CLS Lowered lateral partition(s)

Ideal for forming linears with a uniform mulching surface.
To adjust the alignment of the planters, add the IOP-PLOT option.

Before filling, plan to lay a geotextile felt straddling the two bins at the level of the lowered partitions.

€ 40 Excl. tax
/ container




IOP-PSX Installation on extruded polystyrene panel

Installation on polystyrene weight distribution buffer. Avoids perforation if installing directly on waterproofing.

Check the admissible load per m².

€ 30 - 80 Excl. tax/per container acc. to size of container




IOP-MTP Handling by forklift

Removable trap door concealing an access underneath the container for handling by forklift. Ideal for moving large containers from time to time.

Handle with care!
The loaded container is subject to great stresses when being moved.

€ 160 Excl. tax/per container




IOP-ISOL Wall insulation (PSX)

Fibre-cement already has a low thermal exchange coefficient. However, in areas with extremes of climate, wall insulation can be added.

Wall insulation only slows down the variations in temperature in the clump of soil. Provide protection for your plantation.

€ 40 - 90 Excl. tax/per container acc. to size of container




IOP-TES Hole and crosspiece for secure fixing

Allows the passage and fixing of a previously ground-secured, threaded rod at the base of the container.

The tightening process must be carried out with care to avoid the risk of damaging the container.

€ 30 - 50 Excl. tax/per container



IOP-TEL Hole and crosspiece for lateral fixing

For the fixing of containers to each other or to a wall.

IOP-FR * Raised base

Allows a reduction in the volume and weight of the soil when plants do not require the whole capacity.

* € 20 - 60 Excl. tax acc. to size of container

IOP-PSE ** Useful height reduced by an expanded polystyrene filling

** If installed on casters, feet, pads... ** cost acc. to container size and height to fill



IOP-ARD Edges and rounded corners

Replaces edges and chamfered angles used in standard design.

Ideal for use in nurseries or schools to prevent the risk of injury.

€ 20 Excl. tax /per container